


CEA 370/5

Company	Anchor Pumps Co. Ltd	Customer	Date	2017-04-11
Contact	Celeste Holmes	Contact	List price	On req.
Project		Phone number	Family code	
Project no.		Email	Item no.	

Performance according to ISO 9906 - Annex A

Power datas referred to:

Water, pure [100%] ; 4°C; 62.4lb/ft³; 0.00565m³/h



Operating Data Specification

Flow	0 m³/h
Head	0 m

Hydraulic data (duty point)

Flow	
Head	
Power input	
MEI >= 0,4	

Pump data

Make	Lowara
Type	CEA 370/5
	Single-impeller centrifugal electric pump
Speed	2900
Head H(Q=0)	30.4 m
Suction side	
Discharge side	
Types of installation	Monobloc
Weight	21 kg

Materials / seals

Pump body	Stainless steel / AISI 304
impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Seal casing	Stainless steel / AISI 304

Shaft Seal

Rotating Assembly	V-Ceramic Alumina
Fixed Assembly	B-Carbon
Elastomers	P-NBR
Springs	G-AISI 316
Other Components	F-AISI 304

Motor data

Rated power P2	4.0231 hp	Nom. Speed	2895 rpm
Frequency	50	Phase	3~
Rated voltage	415 V	Rated current	6.44 A
Protection class	IP 55	Insulation class	F
Permitted voltage tolerance +/- 10%			

Dimensions mm

A	54	H2	245
D	174	L	429
DNA	Rp2	L1	172
DNM	Rp1?	W	76
H	224		
H1	113		

Note:

