


6-15 (oil-lubricated)

Voltage	V	100	100	120	200	200	230	230					
Frequency	Hz	50	60	60	50	60	50	60					
Motor	HP	0.54	0.54	0.54	0.46	0.46	0.46	0.46					
	kW	0.40	0.40	0.40	0.34	0.34	0.34	0.34					
Displacement	l/min	50	60	60	50	60	50	60					
	CFM	1.77	2.12	2.12	1.77	2.12	1.77	2.12					
FAD @ 8 bar	l/min	32	37	37	32	37	32	37					
	CFM	1.13	1.31	1.31	1.13	1.31	1.13	1.31					
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8					
	psi	120	120	120	120	120	120	120					
Max. current	A	6.2	6.2	6.2	2.9	2.9	2.9	2.9					
Tank size	litres	15	15	15	15	15	15	15					
	gallon	4	4	4	4	4	4	4					
Weight	kg	26	26	26	26	26	26	26					
	lbs	57	57	57	57	57	57	57					
Noise level	dB(A)/1m	45	45	45	45	45	45	45					
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes					
Duty cycle		50%	50%	50%	50%	50%	50%	50%					



Dimensions (l x w x h)
380 x 380 x 480 mm / 15 x 15 x 18 7/8 inch

¹⁾ Higher pressure available upon request

Technical modifications reserved

JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com

