

# Wireless Receiver

for NetworX Panels



## OVERVIEW

The NetworX Wireless Receiver adds wireless capability to NetworX control panels. Adding a receiver makes these control panels compatible with Interlogix Learn Mode wireless devices. Only three wire connections are required for power and communication to the control panel.

## STANDARD FEATURES

- 48 wireless zones
- 1,000-ft. open-air range
- Compatible with all NX series control panels
- Can be installed in the enclosure or remotely for best reception
- Compatible with a wide range of wireless devices

## Specifications

Compatibility	NX-4, NX-6, NX-8, NX-8E control panels
<b>Features</b>	
Frequency	319.5MHz
Wireless range	1,000 ft. (300m)
<b>Electrical</b>	
Required power	12VDC (provided by panel)
Current draw	55mA max.
<b>Environmental</b>	
Operating temperature	32 to 120°F (0 to 49°C)
Storage temperature	-30 to 140°F (-34 to 60°C)
Relative humidity	85% max., noncondensing
<b>Physical</b>	
Dimensions	4.65 x 3.20 in. (118 x 81mm)
Regulatory	FCC, UL, cUL, UL 985, UL 1023, UL 1610, ULC subject C1023-1874, ULC-S545-02

## Ordering Information

<b>NX-548E</b>	Wireless Receiver for NetworX Panels
----------------	--------------------------------------



interlogix.com

Specifications subject to change without notice.

© 2013 United Technologies Corporation.

All rights reserved.

Interlogix is part of UTC Climate, Controls & Security,  
a unit of United Technologies Corporation.

306-3678 2013/11 (75050)

**North America**  
T 855-286-8889

**Latin America**  
T 561-998-6114