



# Stainless steel AISI 304 pumps for TRANSFER

Ratio 1:1 Flow rate 30 l/min



Stainless steel AISI 304 air-operated pumps for short-medium distance transfer. Ideal for transferring low-medium viscosity fluids such as: antifreeze liquid, windshield washing liquid and chemical products.



## series 600 INOX

Article with seals in	VITON	33360	33396	33300
Compatible fluids		Suitable for antifreeze and windshield washing liquid		
Suction tube lower body		Stainless steel AISI 304		
Suction tube		Stainless steel AISI 304		
Air inlet connection	bsp	F 1/4" G	F 1/4" G	-
Fluid outlet connection	bsp	F 1/2" G	F 1/2" G	-
Air working pressure	bar	6 - 8	6 - 8	-
Average air consumption	l/min	370	370	-
Noise level	dB	81	81	-
Max deliverable oil viscosity	SAE	50	50	-
Bung adaptor		-	standard	33434
Suitable for drums or tanks			 suitable for drums 180-220 Kg	
Packing	N° - m <sup>3</sup>	1 - 0,10	1 - 0,020	1 - 0,29
Weight	Kg	5,3	7,4	11,4
Dimensions (A - B - C)	cm	41 - 0 - 0	41 - 94 - 3,4	41 - 94 - 3,4

**Art. 33445**  
Gun for antifreeze and windshield liquid applicable to kit Art. 33300 equipped with:  
- inlet joint F 1/2"  
- stainless steel rigid terminal with free outlet



PUMP AIR FEEDING PRESSURE

<b>A</b>	<b>B</b>	<b>C</b>
8 bar	6 bar	4 bar
116 psi	87 psi	58 psi

