

BI-DIRECTIONAL FITTING

Swivels 360°	Efficient	Construction Zamac	Flow rate 45 m³/h at 7 bar	Ease of use
-----------------	-----------	------------------------------	---	-------------

		A	B	C	DESCRIPTION	REFERENCE
Bi-directional fitting with regulator for pneumatic tools						
					<ul style="list-style-type: none"> - Can keep the hose straight without restraint. - Improve pneumatic tools handling and use. - Inlet : G 1/4 BSP Gas female - Outlet : G 1/4 BSP Gas male 	
		36	64	43.5	360° bi-directional fitting with regulator and manometer 0 to 10 bar	OP BDMR
					360° bi-directional fitting with regulator	OP BDR
Bi-directional fitting for pneumatic tools						
					<ul style="list-style-type: none"> - Can keep the hose straight without restraint. - Improve pneumatic tools handling and use. - Inlet : 1/4 G BSP Gas female - Outlet : 1/4 G BSP Gas male 	
		35	42.5	43	360° bi-directional fitting with manometer 0 to 10 bar	OP BDM
					360° bi-directional fitting	OP BD

MULTI SWIVEL

Efficient	Swivels 360°	Construction Highly resistant stainless steel body	Ease of use	Non-scratch	ID Passage 8 mm
-----------	-----------------	--	-------------	-------------	---------------------------

		A	B	DESCRIPTION		REFERENCE
Compressed air multi swivel						
				Inlet	Male threaded outlet	
		127	40	G 1/4 female	G 1/4	PFA 085101
		127	40	G 3/8 female	G 1/4	PFA 085102
		127	40	Inlet for Ø 6 mm hoses	G 1/4	PFA 085106
		127	40	Inlet for Ø 8 mm hoses	G 1/4	PFA 085108
		127	40	Inlet for Ø 10 mm hoses	G 1/4	PFA 085110