




HF **HeadlineFilters**

Filter Element: 12-32-70CS

Technical Specification	
Description	Disposable Particulate Filter Element
Materials of Construction	Borosilicate Glass Microfibres bonded with Silica inorganic resin only
Filtration Efficiency	Better than 95.0+% removal of 0.1 micron particles
Air Flow Resistance	Less than 0.6KPa at 6m/min in air at 25°C
Dimensions	I.D. - 12.5mm ± 0.25mm O.D. - 19.0mm ± 1.5mm Length - 32.5mm ± 0.25mm
Strength (dry)	Burst minimum - 5.0 Bar Collapse minimum - 2.0 Bar
Temperature Resistance	-50°C to +500°C maximum air
Chemical Resistance	Resistant to all mineral, vegetable and synthetic compressor lubricants Consult chemical resistance chart for other gases and liquids



For further specific information please contact our Technical Department
This is a guide only

 DO NOT SCALE DRAWING IF IN DOUBT ASK	Filter Element: 12-32-70CS		THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HEADLINE FILTERS. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY, OR IN PART WITHOUT CONSENT IN WRITING.
	Material: Borosilicate Glass Microfibres bonded with Silica inorganic resin only	