



<b>Electrical Data</b>		
Nominal resistance	0.1 ... 100	kOhm
Resistance tolerance	±5	%
Independent linearity	±0.15	% of meas. range
Electrical angle	3600	°
Temperature coefficient of the voltage divider	40	ppm/°C
Recommended wiper current	max. 10	µA
Max. wiper current in case of malfunction	50	mA
Power rating P	2	W/70°C
Min. life (electrical)	1 Mio.	turns
<b>Mechanical Data</b>		
Mechanical range	10	turns
Torque	max. 0.7	Ncm
Min. life (mechanical)	1 Mio.	turns
Operating temperature	-55 ... +125	°C
Storage temperature	-55 ... +125	°C
Protection class	IP50	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

## PD2310

### Applications

- Fork-lifter
- Lifting platform

### Features

- Small dimensions
- 1 Mio. turns
- Excellent linearity ±0.15%
- Extremely little susceptibility to damage

### Options

- Tandem-ganged potentiometer i.e. 2 on one shaft
- Custom shafts design
- Custom bushing design
- 3 turns (PD2303)
- 5 turns (PD2305)

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Telefax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**